




G3 CONSTRUCTION 	STAINLESS STEEL WET 0.78 0.79	QUARRY TILE DRY 0.89 0.92	QUARRY TILE WET 0.73 0.69	QUARRY TILE OIL & WET 0.33 0.32	FROSTED ICE 0.30 0.31	Test done by Satra on <b>August 14, 2023</b> Test method for slip resistance: EN ISO 13287: 2019 (Standard 0.30)
--	----------------------------------	------------------------------	------------------------------	------------------------------------	--------------------------	---

### G3M A9058B-11, 12

Size: 3-16 & 8½-10½

(Women: 2 sizes smaller)

Colour: Black (11), Tan (12)

Height: 8"/20.4 cm

Width: WW



A9058B-11



A9058B-12

- 2 mm waterproof full grain leather (A9058B-11) or nubuck (A9058B-12) upper with triple sealed seams.
- Lightweight and non-conductive composite toe and puncture-resistant plate.
- Breathable and abrasion resistant Cambrelle lining with antimicrobial treatment.
- Removable insole made of PU and memory foam offering breathability, comfort and great shock absorption.
- Extra wide fit for more room and comfort.
- Nylon polycarbonate shank.
- Scuff resistant PU toe cap for increased wear protection.
- Dual density outsole made of natural rubber and lightweight PU core.
- Natural rubber 4Grip slip resisting outsole, on dry, wet, oily, frosted surfaces; resistant to wear and oil.
- Absorb+ heel, absorbing shock impacts during impact and increasing grip.
- Polymer eyelets.
- 90° heel angle.
- Padded tongue and collar for extra comfort.
- High visibility reflective inserts.



4GRIP

ABSORB+

