

G3 CONSTRUCTION	STAINLESS STEEL WET	QUARRY TILE DRY	QUARRY TILE WET	QUARRY TILE OIL & WET	FROSTED ICE	Test done by Satra on August 14, 2023 Test method for slip resistance: EN ISO 13287: 2019 (Standard 0.30)
	0.78 0.79	0.89 0.92	0.73 0.69	0.33 0.32	0.30 0.31	

CRUSHER A9302-11

Size: 3-16 & 8½-10½
(Women: 2 sizes smaller)

Height: 8"/20 cm
Width: WW

Colour: Black (11)

Integrated handle



- 2 mm waterproof full grain leather upper with triple sealed seams with handles for quick donning.
- METATECH System Flex flexible metguard protection, CSA certified, protects the top as well as the sides of the foot.
- Breathable mesh lining with antimicrobial treatment.
- Waterproof and breathable Drylock II membrane.
- 600 g Thinsulate insulation surrounding the foot.
- Composite toe and puncture-resistant plate.
- Removable insole made of PU and memory foam offering breathability, comfort and great shock absorption.
- Dual density outsole made of natural rubber and lightweight PU core.
- Natural rubber 4Grip slip resisting outsole, on dry, wet, oily and frosted surfaces.
- Absorb+ heel, absorbing shock during impact and increasing grip.
- 90° heel angle.
- Padded tongue and collar for extra comfort.
- High-visibility reflective inserts and polymer eyelets.
- Polycarbonate shank.



Breathable Waterproof

