

FREESTYLE CONSTRUCTION	STAINLESS STEEL WET	QUARRY TILE DRY	QUARRY TILE WET	QUARRY TILE OIL & WET	Test done by Satra on July 3, 2024 Test method for slip resistance: EN ISO 13287: 2019 (Standard 0.30)
	0.67 0.71	0.91 0.92	0.63 0.63	0.34 0.33	

FREESTYLE A9294-11, 15
FREESTYLE SLIP-ON A9297-11
 Size: 3-15 & 7½-10½ Height: 4.75" / 12 cm
 Colour A9297: Black (11) Width: W
 Colour A9294: Black (11), Green (15)

- 10 oz resistant canvas upper.
- Steel toe and puncture-resistant plate.
- Breathable and abrasion resistant lining with antimicrobial treatment.
- Removable insole made of PU foam to maximize shock absorption and for a long-lasting comfort.
- Nylon shank.
- Dual density outsole made of natural rubber and lightweight EVA core.
- Natural rubber 4Grip slip-resistant outsole for dry, wet, and oily surfaces; resistant to wear and oil.
- TPU scuff resistant toe cap for increased wear protection.
- Padded tongue and collar for extra comfort.



FREESTYLE A9294-11

FREESTYLE A9294-15



FREESTYLE SLIP-ON A9297-11


4GRIP
