

G3 CONSTRUCTION	STAINLESS STEEL WET		QUARRY TILE DRY		QUARRY TILE WET		QUARRY TILE OIL & WET		FROSTED ICE		Test done by Satra on August 14, 2023 Test method for slip resistance: EN ISO 13287: 2019 (Standard 0.30)
	0.78	0.79	0.89	0.92	0.73	0.69	0.33	0.32	0.30	0.31	

G3T A9060B-11

Size: 3-16 & 8½-10½

(Women: 2 sizes smaller)

Colour: Black (11)

Height: 8"/20.4 cm

Width: WW

Integrated handle



MICROFIBER LINING

- 2 mm waterproof full grain leather upper with triple sealed seams with handles for quick donning.
- Breathable and abrasion resistant microfiber lining with antimicrobial treatment.
- Waterproof and breathable Drylock II membrane.
- 200 g of Thinsulate insulation surrounding the foot.
- Lightweight and non-conductive composite toe and puncture-resistant plate.
- Removable insole made of PU and memory foam offering breathability, comfort and great shock absorption.
- Dual density outsole made of natural rubber and lightweight PU core.
- Natural rubber 4Grip slip resisting outsole, on dry, wet, oily, frosted surfaces; resistant to wear and oil.
- PU scuff resistant toe cap for increased wear protection.
- Nylon polycarbonate shank.
- Polymer eyelets.
- High visibility reflective inserts.
- Extra wide fit for more room and comfort.
- Absorb+ heel, absorbing shock impacts during impact and increasing grip.
- 90° heel angle.
- Padded tongue and collar for extra comfort.



4GRIP

ABSORB+

drylock® Breathable Waterproof II

