

VECTOR CONSTRUCTION 	STAINLESS STEEL WET 0.89 0.78	QUARRY TILE DRY 1.05 1.16	QUARRY TILE WET 0.72 0.75	FROSTED ICE 0.33 0.34	Test done by Satra on December 27, 2017 Test method for slip resistance: EN ISO 13287: 2012 (Standard 0.30)
-------------------------	----------------------------------	------------------------------	------------------------------	--------------------------	--

INNOVA A9255-12

Size: 7-14 & 8½-10½

Height: 8"/20.4 cm

Colour: Brown (12)

Width: W



FLEXIBLE & RESISTANT SHELL

- 2 mm waterproof leather upper with triple sealed seams.
- Lightweight and non-conductive composite toe and puncture-resistant plate.
- Breathable lining with antimicrobial treatment.
- 600 g Thinsulate insulation surrounding the foot.
- Waterproof and breathable Drylock II membrane.
- Removable insole made of PU foam to maximize shock absorption and for a long-lasting comfort.
- Nylon polycarbonate shank.
- TPU molded upper and reinforcement.
- Natural rubber 4Grip slip resisting outsole on frosted surfaces.
- Absorb+ heel, absorbing shock impacts during impact and increasing grip.
- Padded tongue and collar for added comfort.

