

VECTOR CONSTRUCTION 	STAINLESS STEEL WET 0.89 0.78	QUARRY TILE DRY 1.05 1.16	QUARRY TILE WET 0.72 0.75	FROSTED ICE 0.33 0.34	Test done by Satra on <b>December 27, 2017</b> Test method for slip resistance: <b>EN ISO 13287: 2012 (Standard 0.30)</b>
-------------------------	----------------------------------	------------------------------	------------------------------	--------------------------	--

## MAGNETIC

A9237-11

Size: 3-14 & 8½-10½

Height: 8"/20.4 cm

(Women: 2 sizes smaller)

Width: W

Colour: Black (11)



- 2 mm waterproof full grain leather upper with triple sealed seams.
- Scuff resistant TPU toe cap for increased wear protection.
- Lightweight and non-conductive composite toe and puncture-resistant plate.
- 400 g of Thinsulate insulation surrounding the foot.
- Breathable lining with antimicrobial treatment.
- Waterproof and breathable Drylock II membrane.
- Removable insole made of PU offering breathability, comfort and great shock absorption.
- Wide fit for more room and comfort.
- Nylon polycarbonate shank.
- Natural rubber 4Grip slip resisting outsole on frosted surfaces.
- Dual density outsole made of natural rubber and lightweight PU core.
- Absorb+ heel, absorbing shock impacts during impact and increasing grip.
- Polymer eyelets.
- 90° heel angle.
- Padded tongue and collar for extra comfort.



4GRIP

ABSORB+

drylock® Breathable Waterproof II

