



<p>GW6 CONSTRUCTION</p>	<p>STAINLESS STEEL WET</p> <p>0.58 0.46</p>	<p>QUARRY TILE DRY</p> <p>1.21 0.93</p>	<p>QUARRY TILE WET</p> <p>0.58 0.46</p>	<p>Test done by Satra on May 1st, 2018 Test method for slip resistance: EN ISO 13287 : 2012 (Standard 0.30)</p>
-------------------------	---	---	---	--

MARSHALL

S22013-11

Size: 3-16 & 3½-15½

Height: 14"/35.5 cm

(Women: 2 sizes smaller)

Width: N-M-W

Colour: Black (11)

Calf circumference: 18.5"/46.99 cm



90°
heel angle

- Fire resistant waterproof 2mm full grain leather upper with handle for quick donning.
- Rigid internal METATECH System 360° metguard protection, CSA certified, protects the top as well as the sides of the foot.
- Composite toe protector and puncture-resistant insole.
- Pierce-Protect Arch Protection System (PPAPS).
- Breathable and abrasion resistant Cambrelle lining with antimicrobial treatment.
- Waterproof, breathable and resistant to pathogens Sympatex membrane.
- 200 g Thinsulate insulation surrounding the foot.
- Removable STC molded insole made of PU foam with heel pad allowing extra comfort.
- Lock-Fit Ankle Support System increases comfort and prevents ankle rollover.
- Natural rubber scuff resistant bumper toe increasing wear protection.
- Vibram Fire & Ice Goodyear outsole made of natural rubber.
- High visibility reflective inserts.
- Fire resistant Kevlar thread.
- Protective shin pad.
- Collar allowing extra comfort.

