

PROLITE 2.0 CONSTRUCTION 	STAINLESS STEEL WET 0.38 0.54	QUARRY TILE DRY 0.53 0.51	QUARRY TILE WET 0.45 0.53	QUARRY TILE OIL & WET 0.35 0.45	Test done by Satra on May 4, 2018 Test method for slip resistance: EN ISO 13287: 2012 (Standard 0.30)

PROSPECT PROFIBER

A9226-11

A9225-11

Size: 3-17 & 8½-10½

(Women: 2 sizes smaller)

Colour: Black (11)

Height: 6"/15.2 cm (A9225)

8"/20.4 cm (A9226)

Width: W

- Chemtech waterproof microfiber upper with H₂O Seal sealed seams, resistant to animal fat, blood and most chemicals.
- Steel toe and puncture-resistant plate.
- Breathable Taibrelle lining with antimicrobial treatment.
- Removable, molded PU insole and anti-fatigue latex foam at the heel.
- 90° heel angle.
- Steel shank.
- PU scuff resistant toe cap for increased wear protection.
- Oil resistant lightweight PU outsole.
- Corrosion resistant Corrosion-resistant metal eyelets.
- Padded tongue and collar for extra comfort.
- 200 g of Thinsulate surrounding the foot (A9226).



PROSPECT A9226-11

PROFIBER A9225-11

MADE WITH
3M THINSULATE™ Insulation / Isolation
 A9226 only
 WATER RESISTANT
 IMPERMEABLE



Chemtech



Taibrelle®

